



RHOBA SUPRA B101

(RHOBATEC AZL)

ARTICLE-NO. 110001

Solvent-based protective coating - blue, easily removable peelable coating

APPLICATION

Apply **RHOBA SUPRA B101** with a brush, roller or cup spray gun. The surface to be treated must be dry and clean and free of oil, grease and dust. Pre-cleaning with our products **RHOBA LAVIA L** or **RHOBA LAVIA W** is recommended. Paint mist deposits can be removed beforehand with our products of the **RHOBA SUPRA E** series.

The drying time depends on the application thickness and the ambient conditions: dust dry after approx. 40 minutes, touch dry after approx. 60 minutes. The curing time is approx. 8 - 16 hours. The thicker and more evenly the product is applied, the easier it is to remove the product again. **RHOBA SUPRA B101** can be easily removed by pushing it off with a spatula or similar. If necessary, **RHOBA SUPRA B101** can be applied again.

PRODUCT FEATURES

- Protects metal, wood and plastic surfaces, e.g. tools.
- protects paint spraying equipment that is constantly "painted" unintentionally by paint mist overspray, but also painting equipment, e.g. painting hangers, paint spray guns or similar
- efficient, as it saves costs when used in paint dry-spray booths
- considerably reduces the subsequent cleaning effort
- water-repellent and protects reliably against corrosion and damage

TECHNICAL DATA

Appearance	clear yellow/brownish liquid
Density at 20 °C	approx. 0,96 g/ml
Flash point	approx. 8 °C

Before application, test material compatibility at an inconspicuous area. Follow the cleaning and care instructions provided by the manufacturer. We cannot be held liable for improper use and resulting damages.

STORAGE

Storage temperature: 5-30 °C
Shelf life: 12 months